

# TELETAX SPN



## DESCRIPTION

TELETAX-SPN can be used with almost any PABX which have RS-232 output for printer connection. TELETAX-SPN replacing this printer, offers the following:

- It filters and processes the telephone call data coming from PABX. This enables to define, which calls data will be printed depending on duration and cost.
- The details of each call can be printed immediately after every call's end.
- The calls are stored in the memory and can be printed in detail per extension.
- If the PABX doesn't provide call cost information, TELETAX-SPN can use its intergrated destination-cost time table to calculate the cost of each call based on number dialled and its duration. For fully accurate call costs TELETAX-SPN can also be used with its optional external cost-pulse detectors interface.

Using its optional Telephone Line interface, TELETAX-SPN can be connected directly to up to 4 PSTN lines, providing the above features without the need of existence of any PABX.

## KEY FEATURES

- It stores the data of up to 3200 calls
- Multiple printing formats as list printing or charge ticket printing
- Check-in and Check-out functions for hotel applications
- Personalized header for bills and charge tickets
- Transparent to Wake up and alert call reports
- All metal, robust construction
- 12 keys keyboard with full travel keys

## TECHNICAL SPECIFICATIONS

Capacity:	Up to 200 Extensions for PABX connection or up to 4 PSTN lines using the Telephone Line Interface
Memory:	3200 call records (expandable)
CPU:	32 Bit RISC
Display:	2x16 characters LCD
Input:	RS-232, 300 to 38400 BAUD
PABX supported:	Easily adaptable to almost any type of PABX
Output:	28 column built in thermal printer
Power supply:	12 - 18 VDC at 8VA (AC adaptor included)
Dimensions:	19 X 13 X 5.5 cm

Call Accounting and Billing System

YOUR  
DISTRIBUTOR